

CORE BITS TILING, CERAMICS, MARBLE

SX

«vacuum brazed technology»



DESCRIPTION AND BENEFITS

- Useful tube length:
 - hex fitting: Ø 6 mm: 32 mm / above: 40 mm
 - M14 fitting: Ø 6 to 18 mm: 35 mm / above: 50 mm
- «Vacuum brazed» segments = even more resistance
- Specially designed for grinders and drills

MATERIALS

Tiling, Ceramics, Granite, Full-body porcelain stoneware, Natural stone

EXPERT ADVICE



For perfect drilling in tiling or stoneware, consider our adapters with pilot drill (ref R04 and R05)



Vacuum brazed diamond segments

Reference	Ø	Connection	Machine	Dry or wet work
SX006N	6	Hexagonal		Dry
SX006NM14	6	M14		Dry
SX008N	8	Hexagonal		Dry
SX008NM14	8	M14		Dry
SX010N	10	Hexagonal		Dry
SX010NM14	10	M14		Dry
SX012N	12	Hexagonal		Dry
SX012NM14	12	M14		Dry
SX014N	14	Hexagonal		Dry

CORE BITS TILING, CERAMICS, MARBLE

Reference	Ø	Connection	Machine	Dry or wet work
SX014NM14	14	M14		Dry
SX018NM14	18	M14		Dry
SX020NM14	20	M14		Dry
SX025NM14	25	M14		Dry
SX032NM14	32	M14		Dry
SX035NM14	35	M14		Dry
SX040NM14	40	M14		Dry
SX045NM14	45	M14		Dry
SX050NM14	50	M14		Dry
SX055NM14	55	M14		Dry
SX060NM14	60	M14		Dry
SX068NM14	68	M14		Dry
SX075NM14	75	M14		Dry
SX080NM14	80	M14		Dry
SX082NM14	82	M14		Dry
SX100NM14	100	M14		Dry
SX105NM14	105	M14		Dry
SX112NM14	112	M14		Dry
SX127NM14	127	M14		Dry