

BLADES ASPHALT, COATING

AS60 Good yield



DESCRIPTION AND BENEFITS

- Designed for machines up to 9.5 kW
- «Drop-shaped» notches on small Ø (up to 230 mm)
- «U» notches and inclined segments for under-cut protection from Ø300 mm

MATERIALS

Asphalt, Coating, Abrasive materials

EN 13236



Reference	Ø	Bore	Segment		Machine	Dry or wet work
			Number	l x w x h		
AS60115/22	115	22,23	9	31 x 2,2 x 10		Dry
AS60125/22	125	22,23	10	31 x 2,2 x 10		Dry
AS60230/22	230	22,23	16	38 x 2,4 x 10		Dry
AS60300/20	300	20	18	40 x 2,8 x 10		Dry Wet
AS60300/25	300	25,4	18	40 x 2,8 x 10		Dry Wet
AS60350/20	350	20	21	40 x 3,2 x 10		Dry Wet
AS60350/25	350	25,4	21	40 x 3,2 x 10		Dry Wet
AS60400/20	400	20	24	40 x 3,6 x 10		Dry Wet
AS60400/25	400	25,4	24	40 x 3,6 x 10		Dry Wet

BLADES ASPHALT, COATING

Reference	Ø	Bore	Segment		Machine	Dry or wet work
			Number	l x w x h		
AS60450/25	450	25,4	28	40 x 3,6 x 10		Wet