

BLADES ASPHALT, COATING

DSLMAXX-A

The DSLMAXX special asphalt coating



EN 13236



DESCRIPTION AND BENEFITS

- Segment design with crossbars:
- better penetration in materials
- reduced lateral friction
- Very high output
- High cutting speed
- Increased longevity
- Straight segments for under-cut protection from diameter 300

MATERIALS

Asphalt, Coating, Abrasive materials

EXPERT ADVICE



DSLMAXX® is a registered trademark and model by DIAM INDUSTRIES

Reference	Ø	Bore	Segment		Machine	Dry or wet work
			Number	l x w x h		
DSLMAXX-A115/22	115	22,23	9	32 x 2,6 x 12		Dry
DSLMAXX-A125/22	125	22,23	10	32 x 2,6 x 12		Dry
DSLMAXX-A230/22	230	22,23	16	38 x 2,6 x 12		Dry
DSLMAXX-A300/20	300	20	20	40 x 2,8 x 12		Dry Wet
DSLMAXX-A300/25	300	25,4	20	40 x 2,8 x 12		Dry Wet
DSLMAXX-A350/20	350	20	24	40 x 3,2 x 12		Dry Wet
DSLMAXX-A350/25	350	25,4	24	40 x 3,2 x 12		Dry Wet
DSLMAXX-A400/25	400	25,4	28	40 x 3,2 x 12		Dry Wet
DSLMAXX-A450/25	450	25,4	32	40 x 3,4 x 12		Wet