

BLADES GRANITE, NATURAL STONE

DSLMAXX-G

The DSLMAXX special granite



EN 13236



DESCRIPTION AND BENEFITS

- Segment design with crossbars
 - improved passage through materials
 - reduced lateral friction
- High cutting speed
- Increased lifetime

MATERIALS

Granite, Hard stone, Natural stone

EXPERT ADVICE



DSLMAXX® is a registered brand and model by DIAM INDUSTRIES

Reference	Ø	Bore	Segment		Machine	Dry or wet work
			Number	l x w x h		
DSLMAXX-G115/22	115	22,23	9	32 x 2,6 x 12		Dry
DSLMAXX-G125/22	125	22,23	10	32 x 2,6 x 12		Dry
DSLMAXX-G230/22	230	22,23	16	38 x 2,6 x 12		Dry
DSLMAXX-G300/20	300	20	20	40 x 2,8 x 12		Dry Wet
DSLMAXX-G300/25	300	25,4	20	40 x 2,8 x 12		Dry Wet
DSLMAXX-G350/20	350	20	24	40 x 3,2 x 12		Dry Wet
DSLMAXX-G350/25	350	25,4	24	40 x 3,2 x 12		Dry Wet
DSLMAXX-G400/20	400	20	28	40 x 3,2 x 12		Dry Wet
DSLMAXX-G400/25	400	25,4	28	40 x 3,2 x 12		Dry Wet

BLADES GRANITE, NATURAL STONE

Reference	Ø	Bore	Segment		Machine	Dry or wet work
			Number	l x w x h		
DSLMAXX-G450/25	450	25,4	32	40 x 3,4 x 12		Wet