

## BLADES CONCRETE, UNIVERSAL MATERIAL

### FX The special saw blade



#### DESCRIPTION AND BENEFITS

- Alternating full and serrated «duos» segments with a height of 12 mm for improved flexibility and high cutting speed
- Reinforced sheet with ventilation holes
- Excellent performance

#### MATERIALS

Concrete, Reinforced concrete, Stoneware, Universal masonry

EN 13236



| Reference | Ø   | Bore  | Segment |               | Machine                                                                               | Dry or wet work |
|-----------|-----|-------|---------|---------------|---------------------------------------------------------------------------------------|-----------------|
|           |     |       | Number  | l x w x h     |                                                                                       |                 |
| FX115/22  | 115 | 22,23 | 9       | 32 x 2 x 12   |  | Dry             |
| FX125/22  | 125 | 22,23 | 10      | 32 x 2,2 x 12 |  | Dry             |
| FX230/22  | 230 | 22,23 | 16      | 38 x 2,6 x 12 |  | Dry             |
| FX300/20  | 300 | 20    | 20      | 40 x 2,8 x 12 |  | Dry Wet         |
| FX300/22  | 300 | 22,23 | 20      | 40 x 2,8 x 12 |  | Dry Wet         |
| FX300/25  | 300 | 25,4  | 20      | 40 x 2,8 x 12 |  | Dry Wet         |
| FX350/20  | 350 | 20    | 24      | 40 x 3,2 x 12 |  | Dry Wet         |
| FX350/22  | 350 | 22,23 | 24      | 40 x 3,2 x 12 |  | Dry Wet         |
| FX350/25  | 350 | 25,4  | 24      | 40 x 3,2 x 12 |  | Dry Wet         |