

MIXING MACHINES



USAGE

Mix of construction materials with medium to high viscosity, up to 50 kg: ready-to-use coating, plaster, lime, concrete, cement, full and normal insulation.

DELIVERY CONTENT

Cardboard box containing :

- 1 mixer
- 1 stirring rod M31326

JOBS

Tiler, Painter, Drywaller, Plasterer

Mixer EHR20/2.6S

The universal mixer

RÉFÉRENCE	EHR20/2.6S
CARACTÉRISTIQUES TECHNIQUES	
Engine	Electric 230 V - 1300
Diameter	140 mm
Connection	M14
Capacity	50 kg
Rotation speed	0 - 250 - 450 rpm
Net weight	5,1 kg
Dimensions l x w x h	650 x 235 x 400 mm



50 kg



2 speeds



140mm



MADE IN EUROPE





- Electronic switch – continuous speed adjustment to limit splashing at start-up
- PUR site wire protected by the machine frame



2-speed transmission - rotation speed adapted to each use



Labyrinth protective cover - protection against dirt, stones, splashes



Direct connection M14 - optimal transmission



Wide and ergonomic frame, raised centre of gravity



Damping and protection elements in special rubber

EN OPTION

REFERENCE	DESCRIPTION
M31326	Stirring rod Ø 140 mm ; type M ; capacity 50 kg
CB-32145	Clicmix quick connection for blade
CB-32230	Mixer extension L. 150 mm ; M14 fitting
CB-32210	Mixer extension L. 250 mm ; M14 connection



M31326



CB-32145



CB-32230



CB-32210