

MIXING MACHINES



USAGE

Homogeneous and lump-free mixture of sleeve, sealant and other liquid materials. Specially adapted to liquid smoothing.

DELIVERY CONTENT

Pallet including :
1 mixing station
1 special stirring rod M31640
1 tank 110 l. M32343

JOBS

Tiler, Renovation company

FLOORMIX2300 Mixing Station

Mobile station for large areas

RÉFÉRENCE	FLOORMIX2300
CARACTÉRISTIQUES TECHNIQUES	
Engine	Electric 230 V - 2300
Diameter	225 mm
Connection	M16
Capacity	150 kg
Rotation speed	70 - 130 - 160 - 280 rpm
Net weight	48 kg
Dimensions l x w x h	816 x 594 x 1329 mm



 150 kg

 4 speeds

 225 mm

 MADE IN EUROPE






- Progressive electronic start-up, constant rotation speed, electronic and thermal overload protection
- Switch with dust and restart protection
- Thick-walled tank
- Mixing function with reduced rotation speed and optimal speed adjustment to the material to be mixed
- Transport trolley with handle



EXPERT ADVICE

Pair your mixing station with the ASP-E16 vacuum to avoid dust emissions during pouring and/or start-up



A homogeneous mixture, without lumps or deposits at the bottom and on the sides of the tank



Compact and balanced machine: easy to handle and tilt, precise dosing



Simplified cleaning



Drive unit with blade that can be easily removed from the trolley without tools



Direct connection to the vacuum cleaner : dust-free work during pouring and starting up



4 large steerable wheels for great mobility

EN OPTION

REFERENCE	DESCRIPTION
M31640	Special stirring rod Ø 225 mm for mixing station
CB-32343	110 l tank.
ASP-E16	Wet and dry vacuum cleaner 1600 W
ASP-E35L	Wet and dry vacuum cleaner 1200 W ; class L
ASP-E35M	Wet and dry vacuum cleaner 1200 W ; class M



M31640



CB-32343



ASP-E16



ASP-E35L



ASP-E35M