

SAW MACHINES



USAGE

Ideal machine for tiling and earthenware cutting

DELIVERY CONTENT

Palette including:

- 1 table saw
- 1 wheel kit
- 1 guidance laser
- 1 extension lead
- 1 tools

JOBS

Tiler

TOOLS



For all your ceramics, earthenware and tiling cutting, use the CR70 blade



Table saws CLASS

High performance for demanding professionals

RÉFÉRENCE	CLASS1100S	CLASS900S
CARACTÉRISTIQUES TECHNIQUES		
Engine	Electric 230 V - 1000	Electric 230 V - 1000
Diameter	200 mm	200 mm
Bore	25,4 mm	25,4 mm
Maximum depth of straight cut	40 mm	40 mm
Maximum cutting depth at 45°	40 mm	40 mm
Maximum material size for straight cut	1100 mm	900 mm
Maximum material size diagonal cut	775 mm	636 mm
Rotation speed	2800 rpm	2800 rpm
Net weight	48 kg	41.10 kg
Dimensions l x w x h	1505 x 675 x 1200 mm	1300 x 720 x 940 mm



Patented systems





- Ultra-rugged aluminium frame
- Electrical and thermal protection
- 2 removable wheels for easy transportation



EXPERT ADVICE

To extend the service life of your table saw, remember to clean the water pump after each use: immerse the pump in clean water and let it run for a few minutes unloaded.



Guide laser




45° tiltable cutting head



Adjustable cutting depth



Guide rail equipped with an interchangeable stainless steel track



Cutting head mounted on 8 bearings : absolute cutting precision

EN OPTION

REFERENCE	DESCRIPTION
10010804	Carrying handle
10010799	Window pane holding system 900 mm (CLASS900S)
10010801	Pane retaining system 1100 mm (CLASS1100S)
SP90167/15	Side rail for lateral support
SP90167/85U	Universal 85 side support
10010794	Lateral extension 600 x 500 mm
SP90159	Single extension 3 m ; L + N + E 16A ; std plug/indus socket
RL151	Single extension 5 m ; L + N + E 16A ; industrial plug/industrial
40011199	35 W water pump



10010804



10010799



10010801



SP90167/15



SP90167/85U



10010794



SP90159



RL151



40011199