

SAW MACHINES



USAGE

Chases in concrete or brick walls for the passage of pipes and other electrical wires.

DELIVERY CONTENT

Transport case including:
1 grooving machine
1 kit of 6 spacers th. 2/3/4/5/10/17 mm for assembly of 2 blades
1 assembly/disassembly key

JOBS

Electrician

TOOLS

For concrete cuts, use a TRB. It fits all powerful grooving machines and allows for a clean and fast cut



Grooving machine EMF125.2

Compact and powerful

RÉFÉRENCE	EMF125.2
CARACTÉRISTIQUES TECHNIQUES	
Engine	Electric 230 V - 1700
Diameter	125 mm
Bore	22,23 mm
Depth	30
Working width	30
Rotation speed	7500 rpm
Net weight	3,3 kg
Dimensions l x w x h	463 x 190 x 133 mm




MADE IN EUROPE



Ø 125 mm

↓ 30





- Lightweight, compact and balanced machine with ergonomic design
- Soft electronic start
- Protective cover against dust and debris
- Locking system for quick and easy tool changes



Tool-free cutting depth adjustment. Quick and comfortable



Locking of the suction hose, prevents accidental release during grooving



Groove width adjustable in 1 mm increments adjustable without additional tools



Use of the spacer kit (optional), mount 3 or 4 blades at the same time



Direct connection to vacuum cleaner for better dust extraction

EN OPTION

REFERENCE	DESCRIPTION
ASP-E16	Wet and dry vacuum cleaner 1600 W
ASP-E35L	Wet and dry vacuum cleaner 1200 W ; class L
ASP-E35M	Wet and dry vacuum cleaner 1200 W ; class M
SP0502	Single-phase extension ; 10 m ; L + N + E 16A ; 1.5 mm ²



ASP-E16



ASP-E35L



ASP-E35M



SP0502