

SAW MACHINES



USAGE

Chases in concrete or brick walls for pipes and other wires

DELIVERY CONTENT

Transport case including:
1 grooving machine
1 set of 6 spacers th. 2/3/4/5/10/17 mm for mounting 2 blades
1 assembly/disassembly key

JOBS

Electrician

TOOLS

For concrete cuts, use a TRB. It adapts to all powerful grooving machines and allows for a clean and fast cut



Grooving machine EMF150.1

Compact and powerful

RÉFÉRENCE	EMF150.1
CARACTÉRISTIQUES TECHNIQUES	
Engine	Electric 230 V - 2300
Diameter	150 mm
Bore	22,23 mm
Depth	45
Working width	46
Rotation speed	4300 rpm
Net weight	6,1 kg
Dimensions l x w x h	355 x 210 x 220 mm




MADE IN EUROPE



150 mm



DUST PROTECTION
SYSTEM
MINERAL DUST MAY
CAUSE CANCERS





- Lightweight, compact and balanced machine with ergonomic design
- Progressive electronic start
- Dust and debris protection cover + stainless steel dust extraction hood
- Locking system for quick and easy tool change



EXPERT ADVICE

Thanks to the spacer kits (optional) fit 3 or 4 blades at the same time : no need to use a rotary hammer or a chisel



Tool-free cutting depth adjustment. Fast and comfortable



Blocking of the suction hose, prevents accidental release during grooving



Stainless Steel extraction hood



Groove width adjustable in 1 mm increments adjustable without additional tools



Using the optional spacer kit, mount 3 or 4 blades at the same time



Direct connection to the vacuum cleaner for better dust extraction

EN OPTION

REFERENCE	DESCRIPTION
CB-3744E	Spacer kit for mounting 3 blades on grooving machine
CB-37445	Spacer kit for mounting 4 blades on grooving machine
ASP-E16	Wet and dry vacuum cleaner 1600 W
ASP-E35L	Wet and dry vacuum cleaner 1200 W ; class L
ASP-E35M	Wet and dry vacuum cleaner 1200 W ; class M
SP0502	Single-phase extension ; 10 m ; L + N + E 16A ; 1.5 mm2



CB-3744E



CB-37445



ASP-E16



ASP-E35L



ASP-E35M



SP0502