

SAW MACHINES



USAGE

Intended for dry and wet cutting of mineral materials (concrete, tile, natural stone, etc) for tasks such as opening and cutting in walls, cutting of expansion joints, etc.

DELIVERY CONTENT

Cardboard box containing :
1 cutting unit
1 tool

JOBS

Construction company, Mason, Paver, Landscape gardener

TOOLS

For cutting natural stone, use the MXE blade



Dry and wet cutting unit ETR400.1P

Flexible and powerful for dust-free sawing

RÉFÉRENCE	ETR400.1P
CARACTÉRISTIQUES TECHNIQUES	
Engine	Electric 230 V - 2850
Diameter	400 mm
Bore	25,4 mm
Depth	152
Rotation speed	1950 rpm
Net weight	13.4 kg
Dimensions l x w x h	710 x 224 x 412 mm



MADE IN EUROPE



400 mm

152





- Soft start
- Oil-bath clutch with optimised speed setting
- Motor protection system with carbon brush trip mechanism
- Direct connection to vacuum cleaner, robust metal suction port
- Wide support rollers, precise guidance
- Adjustable handle and hood, ergonomic machine in various working positions
- Easy tool replacement
- Integrated water connection with flow regulator



Cutting depth adjustment device



Rails de guidage CB-3744P000 and CB-3744N000 with manual feed device



Connection to the quick-guide Rail



EN OPTION

REFERENCE	DESCRIPTION
MXE400/25	
CB-3744VW	Sealant for flush cutting: flange and protection guard
CB-3744U000	Depth adjustment device
CB-3744P000	Rail guide L. 1,000 mm
CB-3744N000	Guiding rail L. 2,000 mm with machine retention
ASP-E16	Wet and dry vacuum cleaner 1600 W
ASP-E35L	Wet and dry vacuum cleaner 1200 W ; class L
ASP-E35M	Wet and dry vacuum cleaner 1200 W ; class M
SP0502	Single-phase extension ; 10 m ; L + N + E 16A ; 1.5 mm2



MXE400/25



CB-3744VW



CB-3744U000



CB-3744P000



CB-3744N000



ASP-E16



ASP-E35L



ASP-E35M



SP0502