

SAW MACHINES



USAGE

Intended for wet sawing of mineral materials (concrete, brick, natural stone, etc) for work such as opening and cutting in walls, sawing of expansion joints, etc.

DELIVERY CONTENT

Cardboard box containing:

- 1 cutting unit
- 1 tool

JOBS

Construction company, Mason, Paver, Landscape gardener, Public Works

TOOLS

For concrete cutting, use the MXE blade



ETR400.2P cutting unit

High torque for water sawing

RÉFÉRENCE	ETR400.2P
CARACTÉRISTIQUES TECHNIQUES	
Engine	Electric 230 V - 2850
Diameter	400 mm
Bore	25,4 mm
Depth	152
Rotation speed	1950 rpm
Net weight	11,4 kg
Dimensions l x w x h	710 x 224 x 412 mm



MADE IN EUROPE



400 mm



152





- Opposite direction of rotation to that of the ETR400.1P - advantageous especially for cuts in walls (prevents kick-back effect when cutting from front to back)
- Soft start, stops in case of overload or overheating, maintains a constant speed
- Oil-bath clutch with optimised speed setting
- Motor protection system with cut-off brushes and replacement indicator
- Easy tool replacement
- No dangerous exhaust gases - can be used in enclosed spaces



Integrated water connection, with flow regulator



Overload indicator, breaker carbon change indicator



Adjustable handle and cover, ergonomic in various working positions

EN OPTION

REFERENCE	DESCRIPTION
MXE400/25	
CB-3744VW	Sealant for flush cutting: flange and protection guard
SP0502	Single-phase extension ; 10 m ; L + N + E 16A ; 1.5 mm2



MXE400/25



CB-3744VW



SP0502