

## SAW MACHINES



### USAGE

Ideal machine for cutting Brick, poroton, marble, stone and granite

### DELIVERY CONTENT

Palette including:  
1 table saw  
1 wheel kit  
1 guidance laser  
1 extension lead  
1 tools

### JOBS

Mason

### TOOLS

For optimal cutting, we recommend using an ST80 blade



## Table saw PRIME700S

Special masonry rail saw

| RÉFÉRENCE                              | PRIME700S             |
|----------------------------------------|-----------------------|
| CARACTÉRISTIQUES TECHNIQUES            |                       |
| Engine                                 | Electric 400 V - 4000 |
| Diameter                               | 700 mm                |
| Bore                                   | 25,4 mm               |
| Maximum depth of straight cut          | 275 mm                |
| Maximum cutting depth at 45°           | 180 mm                |
| Maximum material size for straight cut | 615 mm                |
| Maximum material size diagonal cut     | 435 mm                |
| Rotation speed                         | 1 400 - 1 700 rpm     |
| Net weight                             | 118 kg                |
| Dimensions l x w x h                   | 2010 x 900 x 1590 mm  |

 MADE IN ITALY

 700 mm  
 275 mm

### Patented systems





- Light and robust aluminium frame
- Thermal and amperometric protection
- Adjustable cutting depth



Cutting head mounted on 8 bearings = absolute cutting precision



Cutting depth 275 mm



Cutting length gauge for fast serial work



Guiding laser



45° tilting cutting head



Semi-automatic feed by crank: more safety, clean cut

## EN OPTION

| REFERENCE   | DESCRIPTION                                                    |
|-------------|----------------------------------------------------------------|
| 10010804    | Carrying handle                                                |
| 90262       | B-Lock pane retention system                                   |
| SP90167/15  | Side rail for lateral support                                  |
| SP90167/120 | 120 mm side support                                            |
| 10010789    | Lateral extension 600 x 500 mm                                 |
| 10010790    | Lateral extension with rollers 600 x 800 mm                    |
| RL200       | Three-phase extension lead; 5 m; L1 + L2 + L3 + N + E 16A; 2.5 |
| 40011193    | 60 W water pump                                                |



10010804



90262



SP90167/15



SP90167/120



10010789



10010790



RL200



40011193