

SAW MACHINES



USAGE

Ideal machine for cutting 10 and 20 mm porcelain stoneware, tiling and earthenware

DELIVERY CONTENT

Palette including:

- 1 table saw
- 1 wheel kit
- 1 guidance laser
- 1 extension lead
- 1 tools

JOBS

Tiler

TOOLS

We recommend using a CR89 blade, especially for cutting Ceramics slab 20 mm



Table saws PRIME

Ideal for cutting XXL format tiles and paving

RÉFÉRENCE	PRIME100S	PRIME120S	PRIME150S	PRIME200S
CARACTÉRISTIQUES TECHNIQUES				
Engine	Electric 230 V - 2200	Electric 230 V - 2200	Electric 230 V - 2200	Electric 230 V - 2200
Diameter	350 mm	350 mm	350 mm	350 mm
Bore	25,4 mm	25,4 mm	25,4 mm	25,4 mm
Maximum depth of straight cut	110 mm	110 mm	110 mm	110 mm
Maximum cutting depth at 45°	80 mm	80 mm	80 mm	80 mm
Maximum material size for straight cut	1000 mm	1200 mm	1500 mm	2000 mm
Maximum material size diagonal cut	705 mm	845 mm	1060 mm	1410 mm
Rotation speed	2800 rpm	2800 rpm	2800 rpm	2800 rpm
Net weight	88 kg	91 kg	97 kg	103 kg
Dimensions l x w x h	1780 x 900 x 1305 mm	1980 x 900 x 1305 mm	2280 x 900 x 1305 mm	2780 x 900 x 1305 mm

Patented systems





- Aluminium chassis, lightweight and robust
- Adjustable cutting depth
- Electrical and thermal protection



Cutting head mounted on 8 bearings: absolute cutting precision



Cutting length guide rail for quick serial work



Semi-automatic feed by handwheel for greater precision and comfort



Guide laser



45° tiltable cutting head



Adjustable bracket

EN OPTION

REFERENCE	DESCRIPTION
90261	Motor handle
10010804	Carrying handle
90262	B-Lock pane retention system
SP90167/15	Side rail for lateral support
SP90167/100	100 mm side support
SP90167/120	120 mm side support
SP90167/150	Side support 150 mm
SP90167/200	Side support 200 mm
10010789	Lateral extension 600 x 500 mm
10010790	Lateral extension with rollers 600 x 800 mm
SP90159	Single extension 3 m ; L + N + E 16A ; std plug/indus socket
RL151	Single extension 5 m ; L + N + E 16A ; industrial plug/industrial
40011193	60 W water pump



90261



10010804



90262



SP90167/15



SP90167/100



SP90167/120



SP90167/150



SP90167/200



10010789



10010790



SP90159



RL151



40011193