

SAW MACHINES



USAGE

Tile cutting from 4 to 20 mm thick

DELIVERY CONTENT

Cardboard box including:

1 tile cutter

1 spare wheel

JOBS

Tiler

SINTESI tile cutters

THE reference in tile cutters

RÉFÉRENCE	SINTESI133	SINTESI163	SINTESI183	SINTESI193
CARACTÉRISTIQUES TECHNIQUES				
Maximum cutting length	1330	1630	1830	930
Max size of the tile (diagonal)	940 x 940 mm	1152 x 1152 mm	1290 x 1290 mm	655 x 655 mm
Tile thickness	4 - 20 mm	4 - 20 mm	4 - 20 mm	4 - 20 mm
Net weight	28 kg	33 kg	36 kg	24 kg
Dimensions l x w x h	1735 x 410 x 290 mm	2035 x 410 x 290 mm	2235 x 410 x 290 mm	1335 x 410 x 290 mm





- Robust aluminium chassis: both rigidity and lightness
- Guidance by bearings: smooth sliding, the cutting head is perfectly maintained in its axis
- Height-adjustable bar up to 20 mm depending on the thickness of the tiles in order to obtain the best possible performance
- Moreover, it has a thickness of 15 mm for superior precision during long tile cuts
- Magnetic aluminium cutting separator, raised during cutting, it is positioned with a simple movement of the handle for tile separation
- One-piece aluminium square, great readability of the measurements, locking device for quick adjustment of diagonal cutting



EXPERT ADVICE

Optimal use on smooth tile. For cuts over 15 mm, it is preferable to carry out preliminary tests. If the finish does not satisfy you, we offer a wide range of table saws.



9 ball bearings: extremely smooth and precise movement.



Compact, on wheels, very easy to transport



Design of the lateral supports: very stable cutting of large formats



Quick adjustment of diagonal cutting ; side guide for serial cuts

EN OPTION

REFERENCE	DESCRIPTION
492	Replacement knob Ø 22 x 6 x 4.7 mm
PULSE	Vibrating suction cup PULSE
SOLLEVA	
ULTRAGRIP	
V200	Electric suction cup for handling max 150 kg (horizontally)
GN805	
GN806	



492



PULSE



SOLLEVA



ULTRAGRIP



V200



GN805



GN806