

SURFACE PREPARATION MACHINES



USAGE

Sanding of formwork joints, joints in cast concrete, removal of irregularities, paints, glue residues, smoothing of concrete surfaces, plaster, stoneware

DELIVERY CONTENT

Cardboard box containing :
1 long reach grinder
1 carrying bag
1 tool

JOBS

Painter, Drywaller, Plasterer

TOOLS

For optimal efficiency, we recommend the PNZ grinding cup



Long reach grinder ELS125D

For your work on walls and ceilings

RÉFÉRENCE	ELS125D
CARACTÉRISTIQUES TECHNIQUES	
Engine	Electric 230 V - 1200
Diameter	125 mm
Bore	22,23 mm
Rotation speed	8000 rpm
Net weight	5,3 kg
Dimensions l x w x h	1123 x 275 x 445 mm



MADE IN EUROPE



DUST PROTECTION
SYSTEM
MINERAL DUST MAY
CAUSE CANCERS



125mm





- Particularly suitable for sanding formwork joints
- Soft start, constant rotation speed
- Thermal and electronic overload protection
- Robust machine, optimised work on inclined surfaces and in corners



Upper part of the liftable hood = sanding flush with the walls made easier



Easily changeable transmission flexible. Simple, quick and economical replacement



Ergonomic handle that can be positioned anywhere along the length of the shaft



Direct connection to vacuum cleaner Ø 35 mm, swivel. Suction hose locking system

EN OPTION

REFERENCE	DESCRIPTION
PNZ125	grinding cup diamond concrete epoxy Ø 125
CB-3765A000	Transport trolley 4 swivel wheels
CB-3765B000	300 mm extension for trolley
ASP-E16	Wet and dry vacuum cleaner 1600 W
ASP-E35L	Wet and dry vacuum cleaner 1200 W ; class L
ASP-E35M	Wet and dry vacuum cleaner 1200 W ; class M
SP0502	Single-phase extension ; 10 m ; L + N + E 16A ; 1.5 mm2



PNZ125



CB-3765A000



CB-3765B000



ASP-E16



ASP-E35L



ASP-E35M



SP0502