

SURFACE PREPARATION MACHINES



USAGE

Smoothing, removal of imperfections, planing of plaster and other coatings, sanding of joints on autoclaved aerated concrete. Used with different grinding cups (sponge, levelling, scraper etc)

DELIVERY CONTENT

Transport case including:
1 grinding cup
1 grinding cup holder
1 CB-37722 sponge

JOBS

Façade maker

TOOLS

See in the "optional" section. For external thermal insulation, consider the Special grinding cup CB-37727

EPG400 Trowel

Exclusive product! Large trowelling capacity

RÉFÉRENCE	EPG400
CARACTÉRISTIQUES TECHNIQUES	
Engine	Electric 230 V - 500
Diameter	370 mm
Rotation speed	60 rpm
Net weight	3,5 kg
Dimensions l x w x h	510 x 400 x 340 mm



MADE IN EUROPE



Ø 370 mm





- High yield per m2
- Lightweight and ergonomic, allows intensive work
- Robust vertically-designed motor = long service life
- Perfect weight distribution
- Rotation speed perfectly suited for grinding and floating work
- Scraped finish with optional grinding cup



Ergonomic design with bail handle



50% time saved

EN OPTION


REFERENCE	DESCRIPTION
CB-37721	Green base (velcro)
CB-3772H	
CB-37724	Scraper (scraped finish)
CB-37725	Fine synthetic sponge grinding cup (smooth finish)
CB-37726	Grinding cup for dressing walls (concrete finish)
CB-37727	Grinding cup sanding I.T.E.
CB-37728	Float (flattened finish)
CB-37729	Grinding cup felt (smooth finish)
CB-3772A	Coating scraper hard (concrete finish)
CB-3765C	Wall support w x h max 1600 x 2900 mm
CB-37433	Balancer 5-9kg
SP0502	Single-phase extension ; 10 m ; L + N + E 16A ; 1.5 mm2



CB-37721



CB-3772H



CB-37724



CB-37725



CB-37726



CB-37727



CB-37728



CB-37729



CB-3772A



CB-3765C



CB-37433



SP0502